

# CURLED TRAIL

## TECHNICAL DATA SHEET



SCHOOLS



SLED  
DRILL



CROSSFIT



MODERATE  
WEIGHTS



FUNCTIONAL  
TRAINING

### OTHER APPLICATIONS

COMMERCIAL AREAS - EXHIBITIONS - COMMON SPACES -  
RELAX - GROUP ACTIVITIES - LANDSCAPES



### FINISHING



CurledTrail

### DIMENSIONS AND TOLERANCES

<b>Thickness (mm)</b>	10mm*			
<b>Length - Roll (m)</b>	5m	10m	15m	20m
<b>Width - Roll (m)</b>	2m	2m	2m	2m
<b>Tolerances</b>	Length & Width $\pm$ 1,5%   Thickness $\pm$ 5%			



## COMPOSITION

<b>Yarn Type</b>	5200 dTex. Bicolour Green 100% PE with UV resistance	
<b>Gauge</b>	3/16"	
<b>Yarn Height</b>	15mm (+/-5%)	
<b>Stitch rate</b>	300s/m (63000/m <sup>2</sup> )	
<b>Primary Backing</b>	100% Polypropylene fabric	
<b>Secondary Backing</b>	Styrene Butadiene Rubber (SBR)	
<b>Fire Behaviour</b>	Efl	EN 13501

\* The wire has a height of 15mm, but since it is curled has a total thickness of 10mm.

\*Its composition and appearance can change while maintaining its behavior and performance.